

# Si-Ge Nano-structured with Tungsten Silicide Inclusions

**Jon Mackey**

Mechanical Engineering,  
University of Akron

**Alp Sehirlioglu**

Materials Science and Engineering,  
Case Western Reserve University

**Fred Dynys**

RXC, NASA Glenn Research Center


NASA Cooperative Agreement: NNX08AB43A

The  
University  
of Akron



CASE WESTERN RESERVE  
UNIVERSITY EST. 1826

think beyond the possible















### Objectives

- Investigate composite strategies with proven Si/Ge thermoelectrics.
- Validate theoretical modeling for silicide inclusion in Si/Ge, requires 10nm inclusions.
- Develop reliable uncertainty analysis for thermoelectric transport properties.
- Study thermal stability of composites.

$$\text{Material } ZT = \frac{\alpha^2 \sigma}{\lambda} T$$

$$\lambda = \lambda_{Elec.} + \lambda_{Lattice}$$

### Test Matrix

2% Dopant P-Type, B N-Type, P		Si/Ge at% Ratio		
		70/30	80/20	90/10
Tungsten Silicide Volume Fraction	0%			
	1%			
	2%			
	5%			

### Objectives

- Investigate composite strategies with proven Si/Ge thermoelectrics.
- Validate theoretical modeling for silicide inclusion in Si/Ge, requires 10nm inclusions.
- Develop reliable uncertainty analysis for thermoelectric transport properties.
- Study thermal stability of composites.


$$\text{Material } ZT = \frac{\alpha^2 \sigma}{\lambda} T$$

$$\lambda = \lambda_{Elec.} + \lambda_{Lattice}$$

### Test Matrix


2% Dopant P-Type, B N-Type, P		Si/Ge at% Ratio		
		70/30	80/20	90/10
Tungsten Silicide Volume Fraction	0%			
	1%			
	2%			
	5%			

## Powder Processing




- Planetary Milling
  - 8 Hours @ 300-580 rpm
  - Ball to powder ratio 3-5
- Spark Plasma Sintering (AFRL)
  - 800-1100°C @ 70-90 MPa
  - 5-10 min Hold

## XRD

★ WSi<sub>2</sub>


## SEM



## 1" Diameter






## Sources of Error





Resistivity

Seebeck

Source	Magnitude
Thermocouple radius	0.25 mm
Sample uniformity	$\pm 0.1$ mm
Thermocouple separation	$\pm 0.1$ mm
Caliper resolution	0.01 mm
Statistical variation	Calculated
DAQ voltage uncertainty	50ppm+1.2 $\mu$ V
DAQ current uncertainty	0.2%+0.3mA
Cold-finger effect	Calculated
Wire Seebeck variation	$\pm 3$ %
Statistical variation	Calculated
Absolute temperature	$\pm 2$ K
DAQ voltage uncertainty	50ppm+1.2 $\mu$ V
DAQ temp. uncertainty	50ppm+1.2 $\mu$ V









2% Doped



○ P-type, B

● N-type, P

		Si/Ge at% Ratio		
		70/30	80/20	90/10
Tungsten Silicide Volume Fraction	0%	X	X	X
	1%	X	X	X
	2%			
	5%	X	X	X









2% Doped

○ P-type, B

● N-type, P



		Si/Ge at% Ratio		
		70/30	80/20	90/10
Tungsten Silicide Volume Fraction	0%	X	◆	X
	1%	X	●	X
	2%	X	■	X
	5%	X	▲	X






Si/Ge at% Ratio		
70/30	80/20	90/10

V.F.	0%		
	0%	x	x
	1%	x	x
	2%	▲	■
	5%	x	x





Si/Ge at% Ratio		
70/30	80/20	90/10

V.F.	0%		
	0%	x	◆
	1%	x	●
	2%	x	■
	5%	x	▲








2% Doped

○ P-type, B

● N-type, P

		Si/Ge at% Ratio		
		70/30	80/20	90/10
Tungsten Silicide Volume Fraction	0%	X	●	X
	1%	X	X	X
	2%	▲	■	●
	5%	X	X	X




2% Doped



○ P-type, B

● N-type, P

		Si/Ge at% Ratio		
		70/30	80/20	90/10
Tungsten Silicide Volume Fraction	0%	X	◆ ●	X
	1%	X	●	X
	2%	X	■	X
	5%	X	▲	X



Si-Ge with Tungsten Silicide Inclusions




2% Doped

○ P-type, B

● N-type, P

		Si/Ge at% Ratio		
		70/30	80/20	90/10
Tungsten Silicide Volume Fraction	0%	X	●	X
	1%	X	X	X
	2%	▲	■	●
	5%	X	X	X





2% Doped

○ P-type, B

● N-type, P

		Si/Ge at% Ratio		
		70/30	80/20	90/10
Tungsten Silicide Volume Fraction	0%	X	◆ ●	X
	1%	X	●	X
	2%	X	■	X
	5%	X	▲	X




2% Doped


○ P-type, B

● N-type, P

Si/Ge at% Ratio



Tungsten Silicide Volume Fraction	Si/Ge at% Ratio		
	70/30	80/20	90/10
	0%	×	×
	1%	×	×
	2%	×	×
	5%	×	×





2% Doped  
○ P-type, B


Si/Ge at% Ratio		
70/30	80/20	90/10
×	◆	×
×	●	×
×	■	×
×	▲	×



Dopant Segregated

Dopant Re-distributed

N. Savvides & D.M. Rowe, J. Phys. D: Appl. Phys. **14** (1981)  
D.M. Rowe & N. Savvides, J. Phys. D: Appl. Phys. **12** (1979)



### Conclusion

- Silicide phase successfully reduces lattice thermal conductivity.
- Increased ZT for silicide composites as compared to baseline Si/Ge.
  - Need to control oxygen contamination to match baseline Si/Ge to RTG.
- Tungsten silicide phase offers tuning of carrier concentration.
- Silicide phase does not hinder thermal stability.


### Acknowledgements

Tom Sabo, Ray Babuder, Ben Kowalski, Clayton Cross  
NASA Glenn Research Center

Dr. Michael Cinibulk  
AFRL Wright Patterson Air Force Base

Dr. Sabah Bux, Dr. Jean-Pierre Fleurial  
JPL

NASA Cooperative Agreement:  
NNX08AB43A



The  
University  
of Akron



CASE WESTERN RESERVE  
UNIVERSITY EST. 1826  
think beyond the possible™